

S7 COMBINES

S7 600, S7 700, S7 800, and S7 900



JOHN DEERE



HARVEST

THE ALL NEW S7 COMBINE



READY

A large green combine harvester is shown from a side profile, moving through a field of mature, golden wheat. The harvester's long, horizontal header is visible, with its cutting mechanism partially submerged in the grain. The operator's cab is on the left side of the machine. The background is a vast, open field stretching to the horizon under a bright, overcast sky with soft, white clouds. The overall scene conveys a sense of agricultural readiness and productivity.

- 4-5 S7 Overview
- 6-7 Power and Productivity
- 8-9 Grain Management
- 10-11 Ultimate Technology Package
- 12-13 Precision and Automation
- 14-15 Comfort and Convenience
- 16-17 Visibility
- 18-21 Service and Support
- 22-23 Specifications

BEHOLD!

BEAUTY AND THE BEAST





The sleek, new lines. The grain-eating heart. The rugged dependability. When we built the all new S7 Combine from the ground up, we looked to its legendary big brother – the X9. Borrowing some of the best X9 features, we gave the S7 the same cab, with more comfort and visibility. We stuffed it with smart guidance and automation tools to increase productivity and decrease stress. And we gave it improved grain loss sensing and residue management system. Together, it all adds up to the most advanced, comfortable, and capable S7 Combine ever built.

IT'S THE SMART POWER PLAY

John Deere PowerTech™ 13.6L engine

Ag built for ag work in the toughest conditions. The turbo-charged, 830 cubic inch power plant not only gives you maximum-rated power at lower engine RPM, it also boosts maximum torque by up to 10%¹. More efficiency. More productivity. Less fuel. That's what we call smart power.

10%
LESS FUEL
USED¹

10%
MORE MAX
TORQUE¹

John Deere 9L Engine

With a new generation 9L engine, S7 700 and S7 600 Combines offer improved fuel dosing and key refinements to the EGR system¹. The result? Reduced fuel usage and easier servicing. It's a power plant that offers a giant leap in helping you reduce fuel usage, and machine operating costs.



¹Compared to previous S700 Series models.



Premium PowerCast™ Residue System

Next season's tillage actually starts during this season's harvest, as your combine residue begins returning nutrients to the soil. Using a combination of straight blade knives and a mechanical drive, the PowerCast™ system delivers even residue distribution up to 45 feet (13.7 meters), while conserving up to 15 horsepower.



Improved Grain Loss Sensing

The enhanced grain loss monitoring system- now standard on the S7- has 2X sensors on the cleaning shoe than on previous models, giving you more accurate loss insights.

NO PAIN

Grain Sensing with HarvestLab™ 3000

Grain quality matters. And the best way to monitor it is with HarvestLab 3000. HarvestLab automatically measures – on the go – moisture, protein, starch, and oil values in wheat, barley, canola, corn, soybeans, oats, and rye.

HarvestLab records and maps small grains data as it's harvested. By viewing this data directly in your combine – or in John Deere Operations Center™ – you can:

- Increase profits per bushel by up to \$0.29 per percentage point of protein above 11%¹. Market your grain for highest potential returns and take advantage of premiums for constituent values, such as protein.
- Prepare for the next growing season. Get a \$5 to \$15 per acre profit potential² by knowing your protein and yield. This tells you accurately how much nitrogen was removed, so you know what needs to be replaced to get the best yields next year.
- Reduce input costs and maximize yield and protein. With the right information, you can improve nutrient management or variety choice by simply targeting field areas where high-protein grain was harvested and focusing on areas that didn't reach the quality or yield targets.



¹ US dollars. Based on USDA Wheat Protein Premium and Discount scales. Grain Protein Premium and Discounts vary by geography, time of year, year, and time of comparison.

² US dollars. Based Internal Trial in 2020 Winter Wheat, Kansas, USA. Results could vary by geography, season, and environmental conditions.

ALL GRAIN





Adjustable Unloading Auger Spout

With the Adjustable Unloading Auger Spout, you can adjust auger positions right from your cab. That makes it easier to fill carts or trailers on the go, and reduces unnecessary grain spillage, increasing your overall grain retention.



Cross Auger Shutoff

Optional on S7 Combines, the cross auger shutoff automatically ensures the auger is completely emptied on every unload. This reduces weight in the auger and peak loads when engaging the unloading system. And, by creating less torque on the chain and unloading sprocket at start up, it reduces potential shear pin breakages that cause time-wasting downtime.

MORE **ACRES.** LESS **STRESS.** **AUTOMATICALLY.**

Harvest Settings Automation

It's your crop. You know what you want out of it.
Does your combine?

Harvest Settings Automation¹ – included in the Premium and Ultimate Technology Packages – makes it easier than ever to set the specific outcomes you expect. Using your G5^{Plus} Display, simply set acceptable limits for grain loss, foreign material, and broken grain.

Once set, the combine automatically adjusts itself to deliver the performance you want. No more manually adjusting rotor speed, fan speed, and concave, chaffer, and sieve clearances. The combine does it for you according to outcomes you've already prescribed.

That gets you into crops faster and reduces the things you have to constantly monitor. When set limits are exceeded, your display shows you where the setting adjustment is being made and why.

Plus, your G5^{Plus} Display comes preloaded with a variety of harvest modules, so you customize your harvest run pages to monitor things like grain loss and yield and productivity history. That means less switching from page to page, allowing you to focus on other things.

Ultimate Technology Package Gain up to 20% more productivity²

¹ Available in both Premium and Ultimate license packages and includes factory-installed hardware, such as cameras and more.

² Based on anonymized Ops Center data comparing John Deere combine models with and without Predictive Ground Speed Automation. Productivity represented by tons of crop per hour. Results will vary depending on model, crop and field and operating conditions.

³ Requires ProDrive™ or ProDrive™ XL Transmission.





Predictive Ground Speed Automation

How many more acres could you harvest if your combine were more predictive and less reactive? Find out with the Ultimate Technology Package which includes Predictive Ground Speed Automation³.

Using two forward, cab-mounted stereo cameras – and pre-harvest satellite field images – the S7 generates a predictive yield map and predictively senses crop height and volume. The combine takes this data and automatically adjusts ground speed BEFORE entering changing crop areas.

That means you can maintain peak feed rates all day long, even in inconsistent crop conditions. That helps you increase combine capacity while minimizing grain loss.

By anticipating the crop load, the combine has time to gently adjust speed without the familiar herky-jerky reactive adjustments we've all experienced.

And as new weed detection and terrain inputs feed into ground speed control, the combine can perform speed adjustments beyond crop conditions.

Less stress. More harvested acres. All automatically. Who could've predicted that? Only the S7.

MORE **PRODUCTIVITY?** LET'S GET **PRECISE.**

G5 Advanced Package

More automation means more productivity and less stress. And that's what you get with the G5 Advanced Package, which bundles five of our most advanced guidance and automation technologies into a single, easily renewable license. That gives you not only a lower up-front cost, but also technology that gets better over time, as you'll get automatic access to new features as they are released. The G5 Advanced Package includes:



AutoPath™

Forget guessing which guidance line to use, even in complex fields. No more counting rows or harvesting that row of shame.



AutoTrac™ Turn Automation

Let your combine automatically handle turns – including raising and lowering the header – and enjoy hands-off, stress-free confidence from one pass to the next.




Machine Sync

On-the-go, stress-free unloading in every condition. Work faster, even with inexperienced grain cart operators.



In-Field Data Sharing

Between multiple machines and fields, share guidance lines, coverage maps, as-applied pass-to-pass data, and field totals, without wasteful radio chatter.



Combine Auto Unload

Automatic grain fill positioning lets you focus on other harvesting tasks by giving you more consistent fills and less worry about the grain cart.





G5^{Plus} CommandCenter™ Display

Bigger. Faster. Clearer. The G5^{Plus} Display gives you more space to see and do more, with a 35% larger screen space. A 3x faster processor for faster boots. And a crisp, 1080p high definition resolution gives you visual clarity in any condition¹.

¹ Compared to previous models



John Deere Operations Center Mobile™

Manage your harvest from anywhere with the Operations Center Mobile app. Remotely view harvest information such as yield, moisture, and area worked. You can also remotely view and adjust combine settings. Plus, you can leverage historical map layers, as well as harvest summary information.

THEY SAY OUR NEW CAB HAS THAT

X FACTOR

That's because the same cab that's on industry-leading X9 Combines is the same one we put on the new S7. With improved visibility, this new cab gives you all-day comfort for all-day work. To keep you connected with your combine, we included an integrated G5 CommandCenter™ Display and an integrated StarFire™ Receiver. And the all new primary display is bigger than previous models, giving you more visibility and control.

An all-new swing ladder makes entry and exit faster and easier, and gives you a narrower profile for transit.

More convenience. More control. More comfort. That's how you keep operators at their best... all day long.

COMFORT PACKAGES

| SELECT | PREMIUM | ULTIMATE |
|---|---|--|
| Cloth air suspension seat with mechanical controls and lumbar support | Cloth air suspension seat with electronic controls and lumbar support; 16 degrees of swivel to the left and right | Appointed leather seat with electronic controls and lumbar support; left-hand and right-hand swivel; heated, ventilated; massaging feature |
| Foot rests | Foot rests | Auto-cinching door |
| Heat and air-conditioning vent at the base of the seat | Refrigerator | Foot rests |
| Five cupholders | Touchscreen radio (satellite and smart phone ready) | Refrigerator |
| Accessory rail with tablet mount | Five cupholders | Touchscreen radio (satellite and smart phone ready) |
| USB and power ports | Accessory rail with tablet mount | Five cupholders |
| | USB and power ports | Accessory rail with tablet mount |
| | | USB and power ports |

SUSPENSION PACKAGES

Two packages offer you a choice in seat suspension.

PREMIUM

Cloth seat with air suspension

ULTIMATE¹

Includes ActiveSeat™ II

Significantly reduces vertical motion up to 90% compared to the premium package

¹Only available with the Premium or Ultimate Comfort and Convenience Package.



YEAH, WE WENT LIGHTS

When harvest work stretches into the night, your S7 Combine can light the way, with three Visibility Packages. Mix or match them with your choice of Comfort and Convenience Packages.

SELECT

LED lights
Manual, unheated mirrors
Grain tank mirror
Front sunshade
Front wiper
Backup camera

PREMIUM

LED lights with twice as much output as previous model
LED lights under each wing
Electric and heated mirrors
Grain tank mirror
Front sunshade
Front wiper
Backup camera

ULTIMATE

360-degree LED lights
LED lights under each wing
Electric and heated mirrors
Grain tank mirror
Front sunshade
Right-hand sunshade
Front wiper
Rear-view camera
Grain tank and unloading auger cameras
Lighting on sides of combine and under the grain tank covers

OUT THIS TIME



YOU'VE GOT *CONNECTIONS*



JDLink™ Connected Service

Your S7 Combine comes standard with a JDLink Modem, and you can activate JDLink connected service free from your Operations Center account¹. Once activated, your John Deere dealer offers the connection needed to keep you running when it's crunch time. With your approval, JDLink provides the bridge to proactive and predictive alerts that identify possible issues and from there, the dealer can remotely assess the problem, saving you time and money.

Service ADVISOR™ Remote

Allows your dealer to remotely analyze diagnostic trouble codes in near real time so technicians arrive on-site with the right parts and the right tools to quickly repair your tractor.

Proactive Alerts

Avoid possible downtime by allowing your dealer to remotely monitor your combine. If they spot a possible issue, they can proactively alert you before it becomes a costly, time-eating problem.

Remote Display Access

Lets your dealer remotely and quickly assist you with in-cab display setup and adjustments for optimal tractor performance.



¹ JDLink hardware comes standard with the machine. You can turn on JDLink connected service in your Operations Center account for free. JDLink requires a cellular connection to transfer information from machine to a JDLink website. Consult your John Deere Dealer for coverage availability.

^{*} Images of products may be digital renderings and/or may not include all options, features, and specifications. Actual product may vary by region and is subject to change. See your John Deere dealer for details.

PARTS, SERVICE AND SUPPORT

TO KEEP YOU RUNNING

The John Deere dealer network is here to serve you. If you need a part, attachment, or service, you can head to a local dealer and use their expertise to find the right solution for your budget. They know the ins and outs of your combine and have a clear understanding of your unique needs. You can count on our highly trained technicians to keep you up and running.

**HARVEST
TERMS™**
PARTS, SERVICE, INSPECTIONS

- Buy Now, Pay After Harvest
- Great Low Financing Available**
- Improved Cash Flow & Savings



**JOHN DEERE
FINANCIAL**

Multi-Use Account™

Stop by the One Parts Counter today. We offer a 12-months limited parts and labor warranty* and multiple financing options as needed.**

* 12 month/ unlimited hour warranty on new OEM agricultural parts installed by an authorized John Deere dealer. 6 month/ unlimited hour warranty for all new John Deere agricultural and turn equipment parts. Terms, conditions, exclusions and warranty limitations apply. See John Deere Service Parts Warranty US & Canada and participating dealers for more details.

** Offer ends March 31, 2026. Financing on approved John Deere Financial credit only. Contact your Multi-Use Account merchant or dealer for complete details.

► ADDITIONAL OPTIONS FOR THRESHING AND SEPARATING ENHANCEMENTS



KONDEX® REVOLUTION™ HALF-WIDTH CONCAVES

Versatility to match varying crop conditions. These concaves provide robust, yet gentle threshing ability in tough-threshing crops, like green stemmed-beans. Their half-width size makes them light and easy to change and install. Two-piece bundle options are offered for small grains and are most commonly paired with OEM concaves in positions 2 and 3. Also available in singles and six-piece configurations.

Kondex is a registered trademark of Kondex Corporation.



CONCAVE THRESHING INSERTS

Made for round-bar concaves, these inserts enable flexibility to harvest additional crops by increasing threshing where inserts are installed.



CONCAVE COVER PLATES

Cover plates install on the bottom side of the concave, encourage even distribution of material in the cleaning shoe, and provide additional threshing for small grains.



HEAVY-DUTY SEPARATOR GRATE WITH INTERRUPTER BARS

A solution for high-yielding corn and tough, small grains and rice, the interrupter bars are excellent at breaking apart corn husk and matted straw and help reduce loss in the separator area.



SEPARATOR GRATE COVER

Separator grate covers are recommended for small grains to reduce chaff load and alter distribution of material to cleaning shoe.



SMALL WIRE CONCAVE INSERTS/INTERRUPTER BARS

Add threshing ability and help reduce white caps. Only for use with small-wire concaves and to be installed on the first concave section.

► CAB ENHANCEMENTS



FOOT RESTS

Improve comfort while harvesting with this simple upgrade.



HEATED FLOOR MAT

Keeps you warm by conducting heat directly over your feet from an internal heating element.



TABLET MOUNT

Keep your data in plain sight and secure with an in-cab tablet mount.

Specifications S-Series Combines

| COMBINE MODEL | S7 600 | S7 700 | S7 800 | S7 900 |
|--------------------------------------|--|--|--|--|
| Engine Specifications | | | | |
| Type | John Deere PowerTech™ | John Deere PowerTech™ | John Deere PowerTech™ | John Deere PowerTech™ |
| Displacement | 9.0 L (549 cu in.) | 9.0 L (549 cu in.) | 13.6 L (830 cu in.) | 13.6 L (830 cu in.) |
| Emission Level | Final Tier 4 / Tier 2 (Australia/New Zealand) | Final Tier 4 / Tier 2 (Australia / New Zealand) | Final Tier 4 / Tier 2 (Australia/New Zealand) | Final Tier 4 / Tier 2 (Australia/New Zealand) |
| Rated Engine Speed | 2,200 rpm | 2,200 rpm | 2,000 rpm | 2,000 rpm |
| Rated Engine Power | 249 kW (334 hp) | 300 kW (402 hp) | 353 kW (473 hp) | 405 kW (543 hp) |
| Power Boost @ Rated Speed | 25 kW (34 hp) | 25 kW (34 hp) | 25 kW (34 hp) | 37 kW (50 hp) |
| Max Engine Power Speed | 2,000 rpm | 2,000 rpm | 1,800 rpm | 1,800 rpm |
| Max Engine Power | 285 kW (382 hp) | 343 kW (460 hp) | 402 kW (540 hp) | 460 kW (617 hp) |
| Fuel Capacity | 950 L (250 gal.) | 950 L (250 gal.) | 1,250 L (330 gal.) | 1,250 L (330 gal.) |
| DEF Capacity | 74.2 L (19.6 gal.) | 74.2 L (19.6 gal.) | 74.2 L (19.6 gal.) | 74.2 L (19.6 gal.) |
| Feeding | | | | |
| Drive Type | Fixed or Variable | Fixed, Variable, or Multi-Speed | Fixed or Multi-Speed | Fixed or Multi-Speed |
| Conveyor Chain Slat Type | Cast Iron | Cast Iron | Cast Iron | Cast Iron |
| Width | 139.7 cm (55 in.) | 139.7 cm (55 in.) | 139.7 cm (55 in.) | 139.7 cm (55 in.) |
| Length | 172.5 cm (67.9 in.) | 172.5 cm (67.9 in.) | 172.5 cm (67.9 in.) | 172.5 cm (67.9 in.) |
| Feed Accelerator, Stone Trap (FAST) | Standard | Standard | Standard | Standard |
| Reverser | Standard | Standard | Standard | Standard |
| Threshing/Separating | | | | |
| Separator Type | Rotary | Rotary | Rotary | Rotary |
| Rotor Length | 312 cm (123 in.) | 312 cm (123 in.) | 312 cm (123 in.) | 312 cm (123 in.) |
| Rotor Diameter | 76.2 cm (30 in.) | 76.2 cm (30 in.) | 76.2 cm (30 in.) | 76.2 cm (30 in.) |
| Rotor Speed Range (High / Low) | 400-1,000 / 210-530 rpm | 400-1,000 / 210-530 rpm | 400-1,000 / 210-530 rpm | 400-1,000 / 210-530 rpm |
| Rotor Threshing Concave Area | 1.1 m² (11.8 sq ft) | 1.1 m² (11.8 sq ft) | 1.1 m² 11.8 sq ft | 1.1 m² 11.8 sq ft |
| Rotor Separation Grate Area | 1.54 m² (16.6 sq ft) | 1.54 m² (16.6 sq ft) | 1.54 m² (16.6 sq ft) | 1.54 m² 16.6 sq ft |
| Discharge Separation Grate Area | 0.36 m² (3.9 sq ft) | 0.36 m² (3.9 sq ft) | 0.45 m² (4.8 sq ft) | 0.45 m² 4.8 sq ft |
| Cleaning | | | | |
| Front chaffer | 0.5 m² (5.4 sq ft) | 0.5 m² (5.4 sq ft) | 0.5 m² (5.4 sq ft) | 0.5 m² (5.4 sq ft) |
| Front Chaffer Extension (Code: 8496) | N/A | N/A | 0.8 m² (8.6 sq ft) | 0.8 m² (8.6 sq ft) |
| Chaffer | 2.5 m² (26.9 sq ft) | 2.5 m² (26.9 sq ft) | 2.5 m² (26.9 sq ft) | 2.5 m² (26.9 sq ft) |
| Sieve Area | 2.1 m² (22.6 sq ft) | 2.1 m² (22.6 sq ft) | 2.1 m² (22.6 sq ft) | 2.1 m² (22.6 sq ft) |
| Total Cleaning Area (louvered) | 5.1 m² (54.9 sq ft) | 5.1 m² (54.9 sq ft) | 5.9 m² (63.5 sq ft) | 5.9 m² (63.5 sq ft) |
| Cleaning Fan Speed | 620-1,350 rpm | 620-1,350 rpm | 620-1,350 rpm | 620-1,350 rpm |
| Grain Handling | | | | |
| Grain Tank Size | 10,600 L (300 bu) | 10,600 L (300 bu) | 14,100 L (400 bu) | 14,100 L (400 bu) |
| Unloading Auger Length | 6.9, 7.9, or 8.7 m (22.5, 26, or 28.5 ft) | 6.9, 7.9, or 8.7 m (22.5, 26, or 28.5 ft) | 6.9, 7.9, or 8.7 m (22.5, 26, or 28.5 ft) | 6.9, 7.9, or 8.7 m (22.5, 26, or 28.5 ft) |
| Peak Unloading Rate | 127 L/s (3.6 bu/sec) | 150 L/s (4.2 bu/sec) | 150 L/s (4.2 bu/sec) | 150 L/s (4.2 bu/sec) |
| Base Weight – Less Head | | | | |
| Front Axle | 9,858 kg (21,737 lb) | 10,366 kg (22,857 lb) | 11,116 kg (24,511 lb) | 11,116 kg (24,511 lb) |
| Rear Axle | 9,646 kg (21,269 lb) | 9,476 kg (20,895 lb) | 11,170 kg (24,630 lb) | 11,170 kg (24,630 lb) |
| Total Machine | 119,504 kg (43,006 lb) | 19,842 kg (43,752 lb) | 22,286 kg (49,141 lb) | 22,286 kg (49,141 lb) |

| | S7 600 | S7 700 | S7 800 | S7 909 |
|---|--------|--------|--------|--------|
| TRACKS | | | | |
| 36 inch John Deere Tracks (MI) | | X | X | X |
| 30 inch John Deere Tracks (MI) | | X | X | X |
| FRONT TIRES | | | | |
| 520/85R42 157A8 R-1 Dual (FS/GY) | X | X | | |
| 520/85R42 162A8 R-2 Dual (FS/GY) | X | X | X | X |
| IF 520/85R42 CFO 169B R-1W Dual (GY) | X | X | X | X |
| VF 520/85R42 CFO 174A8 R-1W Dual (FS) | X | X | X | X |
| 580/85R42 166A8 R-1W Dual (FS/GY/MT) | X | X | X | X |
| 650/85R38 173A8 R-1W Dual (FS/GY/MT/MI) | X | X | X | X |
| 800/65R32 172A8 R-1W (FS) | X | | | |
| 800/70R38 173A8 R-1W (FS/GY) | X | X | | |
| VF 800/70R38 CFO 193B R-1W (FS) | X | X | X | X |
| LSW 800/55R46 190D R-1W (GY) | X | X | X | X |
| IF 900/65R32 CFO 191A8 R-2 (GY) | X | X | X | X |
| VF 900/60R32 CFO 193B R-1W (FS) | X | X | X | X |
| LSW 1100/45R46 CFO 190A8 R-1W (GY) | X | X | X | X |
| IF 1250/50R32 CFO 188B R-1W (FS) | X | X | X | X |
| LSW 1250/35R46 CFO 195A8 R-2 (GY) | X | X | X | X |
| REAR TIRES | | | | |
| 600/70R28 161A8 R-1W (FS/GY/MT) | X | X | | |
| 620/75R26 166A8 R-1W (FS/GY) | X | X | X | X |
| VF 620/75R26 172A8 R-1W (FS) | X | X | X | X |
| VF 620/70R26 RIW 173A8 (MI) | X | X | X | X |
| LSW 710/60R30 177A8 R-1W (GY) | X | X | X | X |
| VF 710/65R26 177D R-2 (GY) | X | X | X | X |
| 750/65R26 166A8 R-1W (FS/GY/MT) | X | X | X | X |
| VF 750/65R26 177B R-1W (FS) | | X | X | X |
| VF 750/65R26 CFO+ RIW 180A8 (MI) | X | X | X | X |

Low Sidewall (LSW) Drive-and-Steer Tires

You'll find some of the smoothest performance imaginable from our new LSW drive-and-steer tires. They offer a similar benefit solution as a track machine in a tire offering. That means you get superior traction and flotation when harvesting in soft, wet soil conditions. Also, they greatly reduce compaction and stubble damage to the tire. If that's not all, the LSW tires allow you to maintain transport speed without tire hop.

A 580/85R42 RIW dual tire option is available on a universal rim that can be dished in or out without axle spacers.

Whether you need to curb **compaction**, reduce rutting, or simply want greater traction when tackling muddy fields, John Deere offers you multiple flotation choices. You're sure to find a flotation system that will fit your operation and your budget.





Supported by one of the most responsive dealer networks in the business

Nobody cares more about keeping your equipment in solid working order than your John Deere dealer. With a complete inventory of genuine John Deere parts, highly trained service technicians, and a thorough understanding of your business, your John Deere dealer knows how to keep you and your equipment up and running.

A strong name in equipment, and a strong dealership network: get it all with John Deere.

This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification and design of all products described in this literature without notice. John Deere, the leaping deer symbol, and green and yellow trade dress are trademarks of Deere & Company Copyright 2025 Deere & Company.



JOHN DEERE